



# SS25 HD

Revised: 10/19/11

## CAMERAS & LENSES

- 14 GVG LDK8000 CCUs
- 14 GVG LDK8000 Worldcam Cameras
- 8 Large Lens Adapters
- 3 Canon HD 100x Zoom Lenses
- 5 Canon HD 86x Zoom Lenses \*
- 4 Canon 21x HH Lens
- 1 Canon 22x7.8 HH Lens
- 2 Canon 11x4.7 Wide Angle Lenses
- 2 Fuji 13x4.5 Wide Angle Lenses
- 1 LDK 6200 SuperMo Camera
- 1 HD Varicam w/Fuji 13x Lens
- 2 Clock Camera
- 8 Vinten Vector 70 Pan Heads with Matthews Tripods
- 7 Vinten Vision 20 HH Tripods & Panheads

*Truck wired for 24 CCUs*

*\* lenses Sportvision modified*

## PRODUCTION

- GVG Kalypso Switcher
- Abekas DVEous Dual Twin HD DVE with CPL control
- GVG 110 HD Switcher
- 172x160 HD SDI Video Router
- 255x320 SD Monitor Router
- Virtual Monitor Wall

## MAIN AUDIO

- Calrec Alpha Digital Audio Console
- 86 dual layer faders
- w/Bluefin DSP Processing
- 32x32 Analog Stereo Audio Router
- 224x224 AES Audio Router
- Analog & AES Internal Cross Conversion Capability
- 2 Day Sequerra Upmix Surround Audio Decoder
- 2 Day Sequerra Downmix Surround Audio Encoder
- 1 Day Sequerra 4 Channel Stereo Synthesizer
- Dolby Digital 571, 572 Encoder & Decoder, 570 Multitool
- 2 Digicart E
- 1 Denon CD Player
- 1 D&K Digital Audio Scope
- Blue Sky Monitor Speakers, L-C-R-LS-RS-Subwoofer
- 2 Lance ADX-2400 D Cobranets

## MICROPHONES

- 12 Sennheiser MD46 Stick Microphones
- 8 Sennheiser HMD-25-1 Announcer Headsets
- 8 Sennheiser MKH-816P Long Shotgun Microphones
- 8 Sennheiser MKH-416P Short Shotgun Microphones
- 6 Sony ECM-55b Lavalier Microphones
- 6 Sony ECM-66b Lavalier Microphones
- 12 Line Amps

## GRAPHICS

Upon Request

## POWER REQUIREMENTS (per unit)

- 208 volts, 3 phase,
- A-Unit requires 1 - 200 amp service
- B-Unit requires 1 - 225 amp service or 2 - 200 amp service

## DIMENSIONS

- 53' long x 13' 6" high x 8' 6" wide (A & B units)
- 82' 4" long x 13' 6" high x 19' wide - expanded w/tractor (A & B units)
- 62' 4" long x 13' 6" high x 19' wide - expanded without tractor (A & B units)
- 53' long x 13' 6" high x 8' 6" wide (D unit)
- A Unit: Tractor# PA AF45043 / Trailer# PA PT7891J
- B Unit: Tractor# IN 410750 / Trailer# PA PT1896R
- D Unit: Tractor# IN 410748 / Trailer# PA PT6759J
- Total Weight per unit 80,000 lbs

## RECORDING & PLAYBACK

- 1 Panasonic DVC-Pro AJHD 1700 VTR
- 1 Panasonic DVC-Pro AJHD 1800 VTR
- 1 Sony DVW-A500 Digibeta VTR
- 6 EVS HD LSM XT[2] - 4 Channel (2 In, 2 Out Server)
- 3 EVS HD LSM XT[2] - 6 Channel (2 w/Supermo Option)
- 1 EVS XT [2] Spot Box - 4 channel
- Sport Net HUB for EVS LSM & Spot Box
- 1 EVS XF2 File Transfer System w/Esata/IDE Drive Docks
- 1 EVS IP Director System
- 4 Lance Slo-Mo Controllers
- 4 DVD Burners

## COMMUNICATIONS

- Telex ADAM Matrix Intercom
- 12 Wet RTS TW PL Channels
- 12 IFB Channels
- RVON -VOIP Adapter
- 4 Gentner QKTS
- 3 Telos One Interfaces
- 12 RTS IFB Beltpacks
- 36 RTS BP-325 Dual Listen Beltpacks
- 10 RTS SPK-300 Biscuit Box User Stations
- 45 Beyer DT-108 Single Muff Headsets
- 20 Beyer DT-109 Dual Muff Headsets
- Headset numbers include camera headsets*
- 6 Daltec Talent Talkback Boxes
- 12 Motorola Walkie Talkies with Base Station
- Lucent Partner II Phone System - 16 lines

## SUPPORT EQUIPMENT

*SD Output of all sources, PGM, PST, M/Es & TX*

- 18 GVG Upconverters
- 4 GVG HD Color Correctors
- 4 Cobalt 9321 Embedders
- 18 GVG HD/SD Frame Syncs
- 20 GVG NTSC to Digital Converter Frame Syncs
- 20 GVG SD to NTSC Encoders
- 12 Outboard Router Heads
- 4 AJA - FS1 Cross Converters
- 1 Frequency Agile TV Modulator
- 2 Frequency Agile TV Demodulator
- 1 Direct TV HD DSS Receiver
- 2 Time Code Reader / Generator

## CABLE

- 10 500ft. Mini-Triax
- 10 250ft. Mini-Triax
- 10 100ft. Mini-Triax
- 2 50ft. Mini-Triax
- 2 500ft. DT-12 Audio Mult
- 10 250ft. DT-12 Audio Mult
- 10 100ft. DT-12 Audio Mult
- 24 125ft. 5-wire Coax Loom
- 2 125ft.10-wire Coax Loom
- 5 Triax Coax Adapters (sets)

## OUTBOARD MONITORS

- 6 20" LCD Flatscreen Monitors (HD/SD Analog Capable)
- 10 13" Color Monitors ( SDI 4x3 or 16x9)
- 10 9" Color Monitors (Analog/SDI 4x3 or 16x9)